PATENT COOPERATION TREATY

PCT

REC'D 18 MAR 2005

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY:

(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference					
P81462PC00ER	FOR FURTHER A	ACTION	See Form PCT/IPEA/416		
International application No. PCT/GB2004/000951	International filing date 08.03.2004	(day/month/year)	Priority date (day/month/year) 14.03.2003		
International Patent Classification (IPC) or national classification and IPC					
E02D27/42, E02D13/04					
Applicant CEMENTATION FOUNDATIONS SKANGKA LIMITED					
CEMENTATION FOUNDATIONS SKANSKA LIMITED et al.					
This report is the international preliminary examination report, established by this International Preliminary Examining Authority under Article 35 and transmitted to the applicant according to Article 36.					
2. This REPORT consists of a total of 5 sheets, including this cover sheet.					
	·				
<u> </u>					
	Sheets of the description, claims and/or drawings which have been amended and are the basic of this report				
and/or streets cor	and/or sheets containing rectifications authorized by this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions).				
☐ sheets which sup	ersede earlier sheets, but w	hich this Authority cons	iders contain an amendment that goes		
beyond the disclo Supplemental Bo	sure in the international api	plication as filed, as indi	cated in item 4 of Box No. I and the		
b. (sent to the Internation	nal Bureau only) a total of (i	indicate type and numbe	er of electronic carrier(s)) , containing a		
sequence iisting ang/c	or tables related thereto, in d ence Listing (see Section 80	Computer readable form	only as indicated in the Complemental		
		or the Administrative	msa acaons).		
4. This report contains indications relating to the following items:					
☑ Box No. I Basis of the	opinion	,			
☐ Box No. II Priority					
☐ Box No. III Non-establi	shment of opinion with rega	ard to novelty, inventive	step and industrial applicability		
☐ Box No. IV Lack of unit	y of invention		•		
☑ Box No. V Reasoned s applicability	statement under Article 35(2 ; citations and explanations	with regard to novelty s supporting such staten	, inventive step or industrial nent		
☐ Box No. VI Certain doo	uments cited	:			
_	ects in the international app				
☐ Box No. VIII Certain obs	ervations on the internation	nal application	•		
Date of submission of the demand		Date of completion of thi	sirenort		
			on open.		
11.01.2005		21.03.2005			
Name and mailing address of the intern	ational	Authorized Officer			
preliminary examining authority: European Patent Office -	D.D. 5010 Detections 0	<u> </u>	and the Pelanest .		
NL-2280 HV Rijswijk - Pa	ys Bas	De Neef, K			
Tel. +31 70 340 - 2040 T: Fax: +31 70 340 - 3016	k: 31 651 epo nl	Telephone No. +31 70 34	10 1210		
		Totephone No. +31 /0 3/	40-434U		

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No. PCT/GB2004/000951

	Box No. i	Basis of the report		
1.	With regar	d to the language , this report is based on the international application in the language in which it was otherwise indicated under this item.		
	☐ This r	eport is based on translations from the original language into the following language , is the language of a translation furnished for the purposes of:		
	□ pu	ernational search (under Rules 12.3 and 23.1(b)) blication of the international application (under Rule 12.4) ernational preliminary examination (under Rules 55.2 and/or 55.3)		
2.	With regard to the elements* of the international application, this report is based on (replacement sheets have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in report as "originally filed" and are not annexed to this report):			
	Description	n, Pages		
	1-12	as originally filed		
	Claims, Nu	umbers ·		
	1-11	as originally filed		
	Drawings,	Sheets		
	1/3-3/3	as originally filed		
	□ a seq	uence listing and/or any related table(s) - see Supplemental Box Relating to Sequence Listing		
3.	☐ The a	mendments have resulted in the cancellation of:		
		e description, pages e claims, Nos.		
	□ the	e drawings, sheets/figs		
		e sequence listing <i>(specify)</i> : y table(s) related to sequence listing <i>(specify)</i> :		
4.	had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).			
		e description, pages e claims, Nos.		
	□ the	e drawings, sheets/figs		
		e sequence listing <i>(specify)</i> : y table(s) related to sequence listing <i>(specify)</i> :		
	* If it	tem 4 applies, some or all of these sheets may be marked "superseded."		

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No. PCT/GB2004/000951

Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)

Yes: Claims

1-11

No:

Claims

Yes: Claims

1-11

No: Claims

Industrial applicability (IA)

Yes: Claims

1-11

No: Claims

2. Citations and explanations (Rule 70.7):

see separate sheet

Inventive step (IS)

Re Item V Reasoned statement with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

- 1.1 The document EP-A-0302707 (D1, cf. Fig. 4) is regarded as being the closest prior art to the subject-matter of claim 1. It discloses an apparatus for positioning an element in a borehole, the apparatus comprising an upper positioning means (7,8) and a lower positioning means (9,10) for adjusting the plan position of the element at upper and lower levels respectively, wherein the apparatus defines an interior space into which, in use, the element is lowered.
- 1.2 The subject-matter of claim 1 differs from this known apparatus in that the positioning means are joined by means of a connection having an adjustable length. The subject-matter of claim 1 is therefore new (Article 33(2) PCT).
- 1.3 D1 is silent about the fixation of the positioning means for adjusting the element (locating frames). These positioning means (7-10) appear fixed to the frame (cf. Fig. 7). The connection does clearly not have an adjustable length. From US-A-1549168 (D2, cf. Fig. 1) it is known to have a connection with adjustable length between two well plugs, allowing manipulation to lower and elevate casings without permitting the escape of fluid from the well. This disclosure is silent about movement in plan direction. JP-A-60141924 (D3, cf. Fig. 1) discloses jacks (5,7) and a measuring assembly (A,9,13,6) to erect a steel pillar in a vertical shaft. The features of claim 1 are separately disclosed in the prior art and employed for different purposes. The specific combination is thus not obvious nor is it a straightforward development. Therefore claim 1 and appended claims 2-8 of the present application are considered as involving an inventive step (Article 33(3) PCT).
- 2. Independent claim 9 claims a method of positioning an element in a borehole with steps using an apparatus which corresponds directly to apparatus comprising the features introduced by product claim 1. Claim 1 is considered to be novel and inventive. Therefore, for the same reasons as mentioned above (cf. paragraphs 1.2 and 1.3), corresponding method claim 9 and appended claims 10,11 of the present application are considered to be new (Article 33(2) PCT) and involve an inventive step (Article 33(3) PCT).
- 3. Claims 1-11 are considered industrially applicable and therefore meet the criteria of Article

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY (SEPARATE SHEET)

International application No.

PCT/GB2004/000951

33(4) PCT.

• :

5

15

20

25

CLAIMS

- 1. An apparatus for positioning an element in a borehole, the apparatus comprising an upper positioning means and a lower positioning means for adjusting the plan position of the element at upper and lower levels respectively, wherein the positioning means are joined by means of a connection having an adjustable length, and wherein the apparatus defines an interior space into which, in use, the element is lowered. 10
 - 2. An apparatus as claimed in claim 1, wherein the upper and lower positioning means each comprise a frame, the frames defining the interior space into which, in use, the element is lowered.
 - 3. An apparatus as claimed in claim 2, wherein the upper and lower positioning means are provided with a guide means for adjusting the plan position of an element within the interior space.
 - 4. An apparatus as claimed in claim 3, wherein the guide means comprises a first and a second pair of rollers which are moveable in mutually orthogonal directions across the interior space.
 - 5. An apparatus as claimed in any preceding claim, wherein the connection comprises wire ropes.
- 6. An apparatus as claimed in any one of claims 1 to 4, 30 wherein the connection comprises chains.



- 7. An apparatus as claimed in anyone of claims 1 to 4, wherein the connection comprises link arms.
- 8. An apparatus as claimed in any preceding claim, wherein the connection comprises a pair of arms provided on one of the positioning means which are telescopically received in a pair of conduits provided on the other positioning means.
- 9. A method of positioning an element in a borehole, the method comprising the steps of:
 - i) placing into the borehole an apparatus comprising an upper positioning means and a lower positioning means for adjusting the plan position of the element at upper
- 15. and lower levels respectively, wherein the positioning means are joined by means of a connection having an adjustable length;
 - ii) lowering the element into an interior space defined by the apparatus to a required depth within the
- 20 borehole; and
 - iii) adjusting the upper and lower positioning means to achieve the desired plan position and orientation of the element.
- 25 10. A method as claimed in claim 9, wherein before placing the apparatus into the borehole, a temporary shaft lining tube is placed within the borehole.
- 11. A method as claimed in claim 10, wherein the
 30 orientation of the apparatus is fixed relative to the
 temporary casing by means of a plurality of locking
 rams.